

7' PREDATOR



Smooth underdecks make for more efficient mowing and less area for rust to begin. Deck rings are standard.

Features:

- 3/8" gearbox plate
- Heavy duty stump jumper & slip clutch
- Laminated tailwheel
- Solid 3/16" (7 Gauge) Deck
- Double Hitch Pin Connection
- Quick Attach
- 3/4" A-Frames
- Dual tail wheels standard
- Cat II. Hitch



CUTTING WIDTH
84"

THE 7' PREDATOR IS A CAT. 2 HITCH WITH A 140 HP GEARBOX AND A CAT. 5 HEAVY DUTY SLIP CLUTCH DRIVELINE.



DUAL TAILWHEELS ARE STANDARD EQUIPMENT.

SPECIFICATIONS

Cutting Width.	84"	Main Gearbox or Divider Box*.	140 hp	Replaceable Skid Shoe	Standard
Transport Width.	90"	Output Shaft Diameter.	2-3/8"	Front Safety Deflectors	Chain Option
Overall Width.	90"	Cut Capacity	4"	Rear Safety Deflectors:	
Overall Length.	100"	Blade Tip Speed:		Rubber Guard Standard with Chain Option	
Overall Height	2" - 12"	540.	17,494 FPM	Weight (Approx).	1750 lbs.
Blade Overlap	3"	Driveline Size.	Cat. 5 w/Slip Clutch	Standard Tires.	Laminated
Hitch	Quick Attach Cat. II	Deck Thickness	3/16"	Dual Tailwheels	Standard
Blade Carrier	Pan Stump Jumpers	Side Skirt.	1/4" x 8"	Deck Ring to Protect Deck	Standard
Horsepower Required (min).	50 hp				

* Gearbox ratings based on field performance.

** The Galvanized gloss level could vary from unit to unit. Modern Ag Products reserves the right to make changes and/or improvements in design and construction of parts or machines shown herein without notice or obligation.