

SUPER HIGHWAY SPECIAL 6' & 7'


CAT. 5 DRIVELINE

- Dual tailwheel option available
- New reinforced tailwheel bracket
- Quick Attach
- 3/4" A-Frames
- Cat. I & Cat II Hitch

6' CUTTING WIDTH
72"

7' CUTTING WIDTH
84"


Features:

- 1/2" gearbox plate
- Heavy duty A-Frame
- New rounded rear deck
- 1/2" x 4" Heavy Duty High Vacuum blades
- 3/8" Deck ring (standard)
- Counter sunk bolt on skid plate
- Upgraded 95 hp gearbox rating
- Heavy duty stump jumper with laminated tailwheel
- Extra Heavy Duty four plate slip clutch protection with flexible top link
- 140 hp gearbox option available


HOT-DIPPED GALVANIZED DECK & FRAME

FRONT & REAR CHAIN GUARD OPTIONAL


Smooth underdecks make for more efficient mowing and less area for rust to begin. Deck rings are standard.

SPECIFICATIONS

Cutting Width. 72"-84"
 Transport Width. 79"-90"
 Overall Width. 79"-90"
 Overall Length. 91"-100"
 Overall Height 2" - 10"

Hitch Quick Attach
 Cat. I & Cat II

Blade Carrier Pan Stump
 Jumpers

Horsepower Required (min) 45 hp
 Gearbox Rating* 95 hp - 140
 hp option
 Cut Capacity 3"

Blade Tip Speed:
 72" 14.995 FPM
 84" 17.495 FPM

Driveline Size. Cat. 5 w/Slip
 Clutch
 Deck Thickness 3/16"

Front Safety Deflectors: Chain Option
 Rear Safety Deflectors: Rubber Guard
 Standard with Chain Option

Weight (Approx):
 72" 1185 lbs.
 84" 1385 lbs.
 Standard Tires Laminated
 Dual Tailwheels Option
 Side Skirt 1/4" x 8"
 Deck Rings to
 Protect Deck Standard

* Gearbox ratings based on field performance.

** The Galvanized gloss level could vary from unit to unit. Modern Ag Products reserves the right to make changes and/or improvements in design and construction of parts or machines shown herein without notice or obligation.