

SUPER SUNSHINE 5', 6', & 7'



Splined input shaft
Slip clutch Standard.

Features:

- New heavy duty 3/8" Gearbox Plate
- Heavy duty stump jumper and laminated tailwheel
- Protected by a splined input shaft slip clutch standard
- Solid top weld
- New smooth rounded rear deck
- Heavy duty tailwheel bracket and boom
- Double steel wall top edge
- One piece body with smooth top
- Upgraded 65 hp gearbox rating with 2"-15 spline output shaft
- Available Quick Attach
- 3/8" A Frames - 3pt.
- 1/2" A Frames - QA
- Cat. I & Cat. II Hitch



SUPER SUNSHINE GEARBOXES HAVE A HEAVY-DUTY 2" 15 SPLINE OUTPUT SHAFT FOR LONGER LIFE AND BETTER CUT CAPACITY. THE SUPER SUNSHINE IS A LONG LASTING CAT. 1 HITCH CUTTER WITH A CAT. 3 DRIVELINE.

**5' CUTTING WIDTH
60"**

**6' CUTTING WIDTH
72"**

**7' CUTTING WIDTH
84"**



Smooth underdecks make for more efficient mowing and less area for rust to begin.

SPECIFICATIONS

Cutting Width.	60" - 72" - 84"	Horsepower Required (min):		Driveline Size.	Cat. 3 w/Slip Clutch
Transport Width.	65" - 75" - 88"	60"	25 hp	Deck Thickness.	3/16"
Overall Width.	65" - 75"- 88"	72"	30 hp	Slip Clutch Protection .	Standard
Overall Length.	100" - 106" - 122"	84"	40 hp	Front Safety Deflectors	Chain Option
Cutting Height	2" - 10"	Gearbox Rating*	65 hp	Rear Safety Deflectors:	
Hitch	Cat. I & Cat. II Quick Attach*	Cut Capacity	2.5"	Rubber Guard Standard with Chain Option	Weight (Approx) 725 lbs. - 865 lbs. - 1189 lbs.
Blade Carrier	Pan Stump Jumpers	Blade Tip Speed:		Standard Tires.	Laminated
Quick Attach	Option	60"	16,519 FPM	Side Skirt.	1/4" x 8"
		72"	14,995 FPM		
		84"	17,300 FPM		

* 5' is only Cat I
 **6' & 7' offer Cat I & Cat II