


THE 4', 5', & 6' COMPETITOR


Features:

- New heavy duty 3/8" Gearbox Plate
- Single piece body with smooth top
- Stronger A-Frame, tailwheel boom and bracket
- Smooth rounded rear deck
- Solid top weld with double steel wall top edge
- Heavy duty stump jumper with laminated tailwheel
- Shear pin protection
- 48 hp gearbox rating
- Slip clutch option available


**4' CUTTING WIDTH
48"**
**5' CUTTING WIDTH
60"**
**6' CUTTING WIDTH
72"**

- Available Quick Attach
- 3/8" A-Frames - 3pt.
- 1/2" A-Frames - QA
- Cat. I Hitch
- Cat. I & Cat. II Hitch for 6' Only



Smooth underdecks make for more efficient mowing and less area for rust to begin.

THE COMPETITOR HAS A CAT. 3 DRIVELINE AND A NEW HEAVY DUTY 3/8" GEARBOX PLATE!

SPECIFICATIONS

| | | | | |
|---------------------------|--|----------------------------|---|------------------|
| Cutting Width. | 48"- 60"-72" | Horsepower Required (min): | 60" | 3/16" |
| Transport Width. | 53"- 65"-75" | 48" | 72" | 3/16" |
| Overall Width. | 53"- 65"-75" | 60" | Slip Clutch Protection . | Option |
| Overall Length. | 83"-100"-106" | 72" | Front Safety Deflectors | Chain Option |
| Cutting Height | 2" - 10" | Cut Capacity | Rear Safety Deflectors: | |
| Hitch | Cat. I Quick Attach For 6' Only Cat. I & Cat. II | Blade Tip Speed: | Rubber Guard Standard with Chain Option | Weight (Approx): |
| Blade Center | Pan Stump Jumper | 48" | 48" | 420 lbs |
| Gearbox Rating* | 48 hp | 60" | 60" | 608 lbs |
| Quick Attach | Option | 72" | 72" | 715 lbs |
| | | Driveline Size. | Tires. | Laminated |
| | | Deck Thickness: | Side Skirt. | 1/4" x 8" |
| | | 48" | | |